

ONXAB1025B

AIR BARRIER WITH IR-PROOF GLASS



TECHNICAL DATA

MECHANICAL

Dimensions (ØxL): 154x21mm (6x0.8in)

Male input 1/2" GAS

Flange with 8 holes

System pressure: 4bar max

Recommended minimum pressure: 2bar

Example of application:

- Input air pressure 1bar, output air pressure 0.2bar, air flow rate 7m³/h
- Input air pressure 2bar, output air pressure 1bar, air flow rate 10m³/h
- Input air pressure 3bar, output air pressure 1.25bar, air flow rate 12m³/h
- Input air pressure 4bar, output air pressure 1.25bar, air flow rate 14m³/h

IR-proof glass

- Thick: 6.6mm (0.3in)
- Operating temperature: 260°C (500°F) max, thermal gradient 108°C (226.4°F) max
- Transmitted IR radiation: 21%

Unit weight: 1.6kg (3.5lb)

DESCRIPTION

Flange designed to create an air barrier in front of the glass, preventing the formation of dust deposits.

PART NUMBER


ONXAB1025B Air barrier with IR-proof glass included for NXW housings

PACKAGE

Model Number	Weight	Dimensions (WxHxL)	Master carton
ONXAB1025B	1.8kg (4lb)	14x25.5x20cm (5.5x10x7.9in)	-

TECHNICAL DRAWINGS

The indicated measurements are expressed in millimetres.



ONXAB1025B